

PRODUCT DATA SHEET & MSDS









DESCRIPTION

Blue Chip Chainlube is specifically designed to lubricate the cutting chain, cutter bar and drive gear of portable chainsaws. It is formulated to provide maximum oil film strength, whilst an effective tackifier additive minimises oil throw-off, even at very high speeds.

PRODUCT FEATURES

- High film strength ensures good lubrication properties.
- Excellent adhesive and cohesive properties.
- Tackiness additive prevents oil from being thrown off.
- Extreme pressure additives minimise wear.

APPLICATION

Formulated to lubricate cutter bar components on all makes of portable chainsaws. Chainlube is also suitable for use in other types of chain driven machinery such as motor cycles and agricultural equipment.

NOTE: Chainlube should be used entirely separate from the engine oil and must therefore NOT be put into the engine or mixed with the engine oil.

TYPICAL PROPERTIES

PROPERTY	UNITS	CHAINLUBE 100	CHAINLUBE 150	ASTM TEST
Viscosity at 40 °C	mm²/s	100	150	D445
Viscosity at 100 °C	mm²/s	11.2	14.9	D445
Viscosity Index	VI	97	99	D2270
Density	°C	0.885	0.890	D4052
Flash Point	°C	210	234	D92
Pour Point	°C	-6	-5	D97

The figures above are not a specification. They are typical figures obtained within production tolerances.

All reasonable care has been taken to ensure that the information contained in this Product Data Sheet is accurate at the date of issue. It should be noted, however, that the information may be effected by changes, subsequent to the date of issue, in the blend formulation or the requirements of any third party specification relating to this product or the methods of application. Final determination of suitability of any





PRODUCT DATA SHEET & MSDS









1. PRODUCT IDENTIFICATION

Product : Chain lubricant Company Identification : CHAINLUBE 100, 150

Substance / Preparation : Preparation

Product Use : Chainsaw cutter bar oil.

2. COMPOSITION

Chemical Composition : Mineral Base Oils and Additives

Hazardous Components : No component is present at sufficient concentration to require a hazardous classification.

3. HAZARDS IDENTIFICATION

Hazards : This material is not considered to be hazardous, but should be handled in accordance with good

industrial hygiene and safety practices.

4. FIRST AID MEASURES

Eye Contact : Flush eyes thoroughly with water. Obtain medical advice if any irritation occurs.

Skin Contact : Wash skin thoroughly with soap and water as soon as reasonably practicable. Remove heavily

contaminated clothing and wash underlying skin thoroughly. If irritation persists obtain medical

attention.

Ingestion : Not expected to be a problem. If large quantities of this product are ingested obtain medical advice.

DO NOT induce vomiting unless directed so by medical personnel. Never give anything by mouth to an

unconscious person.

Inhalation : Avoid excessive inhalation of mists, fumes or vapour. This causes irritation to the nose, throat, and

coughing. Remove person from exposure. If symptoms persist obtain medical advice.

5. FIRE FIGHTING MEASURES

Extinguishing media : In case of fire the use of water sprays, fog or standard foam is recommended. DO NOT USE water jets.

Water may be used to cool nearby heat exposed areas /objects. Avoid spraying directly into storage containers because of the danger of boil-over. Move container away from fire area if you can do it

without risk.

Special hazards : Fires in confined areas should be dealt with by trained personnel wearing approved breathing

apparatus. Toxic fumes may be evolved on burning or exposure to heat.

Protective clothing : Use suitable protective breathing apparatus.

6. ACCIDENTAL RELEASE MEASURES

Personal precautions : Any spillages should be regarded as a potential fire risk. In the event of spillage, remove all sources of

ignition and ensure good ventilation. Spilled material may make surface slippery. Clean up spilled material immediately. It is advised that stocks of suitable absorbent material should be held in

quantities sufficient to deal with any spillage which may be reasonably anticipated.

Environmental precautions : Do not wash product into drainage systems, protect drains from potential spills to minimize

contamination.

In the case of spillage on water, prevent the spread of product by the use of suitable barrier equipment. Recover from the surface. Protect environmentally sensitive areas and water supplies. Minimize contact

of spilled material with soils to prevent runoff to surface waterways.

Small Spills : For small spills clean up the material immediately. Contain and recover spilled material using sand or

other suitable inert absorbent material.

Large Spills : Recovery of large spills should be affected by specialist personnel.

7. HANDLING AND STORAGE

Handling precautions : Avoid contact with skin and observe good personal hygiene. Avoid contact with eyes. If splashing is

likely to occur wear a full face visor or chemical goggles as appropriate. Avoid frequent or prolonged skin contact with fresh or used product. Wash hands thoroughly after contact. Use disposable cloths and discard when soiled. Do not put soiled cloths in pockets. Take necessary precautions against accidental spillage into soil and water. Good working practices, high standards of personal hygiene and plant

cleanliness must be maintained at all times.

Storage precautions : Store under cover away from heat and sources of ignition.





PRODUCT DATA SHEET & MSDS







8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Occupational Exposure Limits: There is no appropriate occupational exposure limit to this material.

Engineering controls : The control measures appropriate for a particular worksite depend on how this material is used and on

the extent of exposure. If vapour, mists or fumes are generated, their concentration in the workplace air

should be controlled to the lowest reasonably practicable level.

Personal Protective Equipment

Respiratory system : Respiratory protection is unnecessary, provided the concentration of vapour, mists or fumes is

adequately controlled. The use of respiratory equipment must be strictly in accordance with any

statutory requirements governing its selection and use.

Hands : Use chemical resistant, impervious gloves.

Eyes : Safety glasses with side shields. Goggles with a face shield may be necessary depending on conditions

of use.

Skin : Disposable outer garments where there is the potential for contact with the material.

9. PHYSICAL PROPERTIES

PROPERTY	UNITS	CHAINLUBE 100	CHAINLUBE 150	ASTM TEST
Viscosity at 40 °C	mm²/s	100	150	D445
Viscosity at 100 °C	mm²/s	11.2	14.9	D445
Viscosity Index	VI	97	99	D2270
Density	°C	0.885	0.890	D4052
Flash Point	°C	210	234	D92
Pour Point	°C	-6	-5	D97

10. STABILITY AND REACTIVITY

Conditions to avoid : Sources of ignition. Thermal decomposition products will vary with conditions. Incomplete combustion

will generate smoke, carbon dioxide and hazardous gasses, including carbon monoxide.

Incompatible Materials : Avoid contact with strong oxidizing agents

Stability : Stable at ambient temperatures. Hazardous polymerization reactions will not occur.

11. TOXICOLOGICAL INFORMATION

Skin contact : Unlikely to cause harm to the skin on brief or occasional contact.

Eye contact : Unlikely to cause more than transient stinging or redness if accidental eye contact occurs.

Ingestion : Unlikely to cause harm if accidentally swallowed in small doses, though larger quantities may cause

nausea and diarrhoea.

Inhalation : At normal ambient temperatures this product will be unlikely to present an inhalation hazard because of

its low volatility. May cause irritation to eyes, nose and throat due to vapour, mists or fumes. May be harmful by inhalation if exposure to vapour, mists or fumes resulting from thermal decomposition

products occur.

12. ECOLOGICAL INFORMATION

Aquatic toxicity : Spills may form a film on water surfaces causing physical damage to organisms; oxygen transfer could

also be impaired.

Biodegradability : This product is inherently biodegradable.

Bio-accumulation : There is no evidence to suggest bio-accumulation will occur.

Mobility : Spillages may penetrate the soil causing ground and water contamination.

13. DISPOSAL CONSIDERATIONS

Disposal Methods : Where possible, arrange for the product to be recycled. Dispose via an authorized person / licensed

waste disposal conductor in accordance with local regulations.

14. TRANSPORT INFORMATION

Road Transport : Not classified as hazardous for transport





PRODUCT DATA SHEET & MSDS







15. REGULATORY INFORMATION

EEC hazard classification : Not classified

DISCLAIMER

The information provided in this data sheet and the health, safety and environmental information it contains, is correct to the best of our knowledge at the date of publication. However, neither Blue Chip Lubricants (Pty) Ltd nor any of its affiliates, accept any liability whatsoever for the accuracy or completeness of the information contained herein. Since this information may be applied under conditions beyond our control, we do not accept any responsibility for the results of its use. Final determination of suitability of any material is the sole responsibility of the user.

