

## Q8 T 1000 15W-40

*Advanced Super Tractor Universal Oil (STOU)*

### Description

Q8 T 1000 15W-40 is a super tractor universal oil that guarantees an excellent performance for your equipment. This versatile single solution oil is used as a lubrication of diesel and gasoline engines, transmissions and final drives and as a brake, clutch and hydraulic fluid. Q8 T 1000 15W-40 meets the requirements of API and ACEA and several OEMs.

### Applications

Q8 T 1000 15W-40 is used as a single lubricant for a wide range of machinery, such as engines, transmissions and final drivers. It is also applied as a brake, clutch or hydraulic fluid. Q8 T 1000 15W-40 is recommended for diesel and gasoline engines. It meets the requirements of API and ACEA and OEMs John Deere, Mercedes-Benz and ZF.

### Benefits

- Excellent transmission lubrication.
- Outstanding hydraulic fluid properties.
- Limits wet brake noise while limiting friction plate wear.
- Excellent response of hydraulic components.
- Excellent anti-foaming properties.

### Specifications, recommendations and approvals

<b>ACEA</b>	E3	<b>MB</b>	227.1
<b>API</b>	CE	<b>Massey Ferguson</b>	CMS M 1135
<b>API</b>	CF	<b>Massey Ferguson</b>	CMS M 1139
<b>API</b>	GL-4	<b>Massey Ferguson</b>	CMS M 1143
<b>Allison</b>	C-4	<b>Massey Ferguson</b>	CMS M 1144
<b>Case New Holland</b>	MAT 3525	<b>Massey Ferguson</b>	CMS M 1145
<b>Case New Holland</b>	MAT 3526	<b>New Holland</b>	NH 024-C
<b>Ford</b>	M2C 134-D	<b>New Holland</b>	NH 030-C
<b>Ford</b>	M2C 159-B	<b>New Holland</b>	NH 410-B
<b>Ford</b>	M2C 159-C	<b>New Holland</b>	NH 420-A
<b>John Deere</b>	JDM J20C	<b>ZF</b>	TE-ML 06B
<b>John Deere</b>	JDM J27	<b>ZF</b>	TE-ML 06C

### Properties

	Method	Unit	Typical
Density, 15 °C	D 4052	g/ml	0,89
Viscosity Grade	-	-	SAE 15W-40
Kinematic Viscosity, 40 °C	D 445	mm <sup>2</sup> /s	100
Kinematic Viscosity, 100 °C	D 445	mm <sup>2</sup> /s	13.6
Viscosity Index	D 2270	-	137
Pour Point	D 97	°C	- 30
Flash Point, P-M	D 93	°C	> 200

The figures above are not a specification. They are typical figures obtained within production tolerances.

### Remarks

Q8 T 1000 SAE 15W-40 has been approved by AGCO/Fendt for use in CVT ML 200 transmissions. Product Data Sheet includes a selection of specifications, for full overview please consult the Q8Oils website.